

Standard Features

- Transfers process pressure accurately without direct contact with process fluids
- Removes the need for expensive instrumentation
- Easily installed and available in five chemically resistant Materials of Construction
- Optional Diaphragm Materials
- Available with 1/4" & 1/2" Bottom Connection Sizes in FNPT & BSPT Female Connection Types
- Thermoplastic Units Rated to 240 PSIG (16 BARG) @ 21°C (70°F)
- 316L S/S Units Rated to 5800 PSIG (400 BARG) @ 21°C (70°F)
- Approved 316 S/S Diaphragm Seals with CRN (Canadian Registration Number)

Model Number	Top Connection Size/Type	Body Material	**Diaphragm Material	Maximum Temperature	Maximum Pressure	Price Gauge Guard Only	
						*¼" FNPT Bottom Connection	*½" FNPT Bottom Connection
AG25A(*)A-PVC- (**)	1/4" FNPT	PVC	**Viton / EPDM / PTFE	140°F / 60°C	240 PSIG / 16 BARG	\$79.00	\$88.00
AG25A(*)A-CPVC- (**)	1/4" FNPT	CPVC	**Viton / EPDM / PTFE	180°F / 82°C	240 PSIG / 16 BARG	\$111.00	\$123.00
AG25A(*)A-PP- (**)	1/4" FNPT	Polypropylene	**Viton / EPDM	180°F / 82°C	240 PSIG / 16 BARG	\$95.00	\$103.00
AG25A(*)A-PVDF- (**)	1/4" FNPT	PVDF	**PTFE	180°F / 82°C	240 PSIG / 16 BARG	\$158.00	\$173.00
AG25A(*)A-S/S-S/S	1/4" FNPT	316 S/S	316 S/S	500°F / 260°C	5800 PSIG / 400 BARG	\$158.00	\$173.00
AG25A(*)A-S/SV-S/S	1/4" FNPT	316 S/S	316 S/S	500°F / 260°C	5800 PSIG / 400 BARG	\$173.00	\$192.00

Optional List Adders

Glycerin Fill & Gauge Mounting Charge

List Adder \$25.00 + Cost of Gauge

See AccuGuard Gauge Product Literature / Price List for Additional Information on Pressure Gauge Product Line

Contact our office for more information on product availability and applications. Other materials available upon request.

Typical Installation

The installation below is a typical installation example only. Consult your engineering department for the appropriate installation for your application or call the factory for advice.

